

## BARIS | Ceiling Lights

### Baris suspended

- Suspended or surface-mounted luminaire
- Unique design
- For lighting offices, conference rooms and other representative rooms
- Lamp housing made of anodized aluminum
- Suspended / suspended or surface mounting
- Cover made of PS, opal or prismatic
- IP20 [9812] or IP44 [9814]
- Available in 3 different colors
- Switchable or DALI - dimmable [46 / 50W variant]



Product number	System performance typ. [W]	Light color	Equipment	Equipment	Luminous flux [lm]	Diffuser	Mounting	Dimensions L-B-H [mm]	EEL
	■	◆	✘					*	
9816■00◆*-✘	16				1300-1600			579-40-53	
9812■00◆*-✘	18/33/50				1700-5900			1140-40-53	
9815■00◆*-✘	39/46	3000/4000	BA = Basic DA = DALI	grau/weiss/ schwarz	3400-4800	Opal / PRM	Abgehängt	1421-40-53	A+
9818■00◆*-✘	18/33/50				1700-5900			1140-40-53	
9819■00◆*-✘	39/46				3400-5300			1421-40-53	

### Article Number | Explanation

Example: HL-■S-HT●-02◆▲C▷

HL	Series
■	System performance typ. [W]
◆	Light color
▲	Beam characteristic
●	Control
▷	CRI
*	Dimensions [mm]
✘	Equipment

For example: HL

HL Series, D=dimmable, 80/100 Watt, 5000K, A2=120°, 60=60°, TA=60°x90°, 8=CRI>80

### TRS-STAR GmbH

Werner-von-Siemens-Str. 1  
76297 Stutensee

Development, Planning  
and Technical Sales  
Dipl. Ing. Frank Werz  
T +49 6233 347-125  
[werz@trs-star.com](mailto:werz@trs-star.com)