

TYTAN 2 | Damp-Proof Tub Lights

TYTAN 2 Basic Multi

- Power supply unit with dedicated microswitch
- Ingress protection: IP67
- Impact resistance class: IK09
- SDCM ≤ 3
- Colour rendering index: Ra > 80
- Body material: PC
- Mounting: surface, suspended
- Certificates: PZH, HACCP



Product number	System performance typ. [W]	Light color	Beam characteristic	Equipment	Luminous flux [lm]	Length [mm]	EEL
	■	◆	▲	✕		▷	●
9708■00◆▶-▲✕	33=19/23/28/33 53=30/38/46/53 62=34/43/52/62 40=23/29/34/40	40 = 4000K		BA = Basic RCR = motion detector 3hEM = emergency light 3h	2500/3000/ 3450/3850 4200/5000/ 5750/6300 4800/5750/ 6550/7300 3050/3650/ 4200/4750	1152 [33/53/ 62W] 1432 [40W]	A++

Article Number | Explanation

Example: HL-■S-HT●-02◆▲C▷

HL	Series
■	System performance typ. [W]
◆	Light color
▲	Beam characteristic
●	Control
▷	CRI
*	Dimensions [mm]
✕	Equipment

For example: HL

HL Series, D=dimmmable, 80/100 Watt, 5000K, A2=120°, 60=60°, TA=60°x90°, 8=CRI>80

TRS-STAR GmbH

Werner-von-Siemens-Str. 1
76297 Stutensee

Development, Planning
and Technical Sales
Dipl. Ing. Frank Werz
T +49 6233 347-125
werz@trs-star.com