

TYTAN 2 | Damp-Proof Tub Lights

TYTAN 2 LED Basic

- Airtight damp-proof tub light
- Ingress protection: IP66
- Impact resistance class: IK09
- SDCM ≤ 3
- Colour rendering index: Ra > 80
- Body material: PC
- Mounting: surface, suspended
- Certificates: PZH, HACCP



Product number	System performance typ. [W]	Light color	Beam characteristic	Equipment	Luminous flux [lm]	Length [mm]	EEL
	■	◆	▲	✕		▷	●
9701■00◆▷✕	30/43/50	40 = 4000K		BA = Basic	3900-6800	1152 [30/43/50W]	A+
				RCR = motion detector		1432 [44/75W]	
	75			LS2 = continuous cabling	10000	1432	A++
				3hEM = emergency light 3h			

Article Number | Explanation

Example: HL-■S-HT●-02◆▲C▷

HL	Series
■	System performance typ. [W]
◆	Light color
▲	Beam characteristic
●	Control
▷	CRI
*	Dimensions [mm]
✕	Equipment

For example: HL

HL Series, D=dimmmable, 80/100 Watt, 5000K, A2=120°, 60=60°, TA=60°x90°, 8=CRI>80

TRS-STAR GmbH

Werner-von-Siemens-Str. 1
76297 Stutensee

Development, Planning
and Technical Sales
Dipl. Ing. Frank Werz
T +49 6233 347-125
werz@trs-star.com