

TYTAN 2 | Damp-Proof Tub Lights

TYTAN 2 LED

- Ingress protection: IP66
- Impact resistance class: IK09
- SDCM ≤ 3
- Colour rendering index: Ra > 80
- Body material: PC
- Mounting: surface, suspended
- Certificates: PZH, HACCP



Product number	System performance typ. [W]	Light color	Beam characteristic	Equipment	Luminous flux [lm]	Length [mm]	EEL
	■	◆	▲	✕		▷	●
9702■00◆▷✕	16/28/35/42/ 47/55/69	30 = 3000K 40 = 4000K 50 = 5000K		BA = Basic RCR = motion detector LS2 = continuous cabling 3hEM = emergency light 3h	2420-11300	1152 [16/28/47/55W] 1432 [35/42/69W]	A++

Article Number | Explanation

Example: HL-■S-HT●-02◆▲C▷

HL	Series
■	System performance typ. [W]
◆	Light color
▲	Beam characteristic
●	Control
▷	CRI
*	Dimensions [mm]
✕	Equipment

For example: HL

HL Series, D=dimnable, 80/100 Watt, 5000K, A2=120°, 60=60°, TA=60°x90°, 8=CRI>80

TRS-STAR GmbH

Werner-von-Siemens-Str. 1
76297 Stutensee

Development, Planning
and Technical Sales
Dipl. Ing. Frank Werz
T +49 6233 347-125
werz@trs-star.com